

## **Key Features**

- Designed to be easy to install, connect, manage and use.
- Embedded Wi-Fi for standard connectivity. No gateway or hub required.
- Remote control and monitoring from anywhere using your smartphone or laptop.
- Supports passage mode, auto-lock mode and passage schedules.
- Lock retains all programming and data even in the event of power outage or internet interruption.
- Secure bi-directional encryption. Low battery warning indicator.





## **5510-WS SERIES**

This Wi-Fi enabled smart lock can be connected directly to the internet without a hub. The 5510-WS series locks is designed to withstand moderate daily traffic in a businesses or commercial setting.

- Store up to 40 weekly access schedules (e.g., M-F, 9-5).
- Set notifications for user entry and alerts for unexpected issues.
- Lockout functionality after 5 incorrect code attempts.
- Utilize temporary codes for guests and visitor management.
- 2 override keys included.
- Works with KeyinCloud ACS wired solutions.



- MiFare Card or KeyFob
- Algorithmic PIN
- Mobile Credentials



## **Product Specifications**

Environment:	For normal internal and external use
Exterior Dimensions:	7% (H) x 2¾ (W) x 2¾ (D) in.
Interior Dimensions:	7% (H) x 2¾ (W) x 2¾ (D) in.
Backset:	2¾ in. (60mm) or 2¾ in. (70mm)
Locking Device:	Tubular latch included (mortise latch available)
Construction:	Zinc alloy, suitable for indoor & outdoor use
Operating Temperature:	-31°F (-35°C) to 151°F (66°C)
Thickness:	1% - 2% in. (35mm - 60mm)
Door Handing:	Non-handed, field reversible
Batteries:	4 AA (not included)
Keyway:	6-pin Schlage C (SF IC core available)
Code Length:	4 - 10 digits
Code Capacity:	Up to 3,500
Communication:	Single band 2.4GHz Wi-Fi (IEEE 802.11b/g/n) with WPA/WPA2
Standards:	Tested to Grade 2 ANSI A156.2/A156.25, UL/ULC fire rating 3 hours
	(when fitted w/ US fire kit)